



Switch, S-Classic, 250V 10AX, 1-way switch, 1 gangs, white

E31/1/2A

Main

Range	S-Classic
Product or component type	Switch
Device application	Control
Switch application	Lighting
Quantity per set	Set of 1

Complementary

Control type	Rocker
Actuator	Rocker
Switch function	1-way
Number of gangs	1 gang
Device mounting	Surface Flush
Rated current	10 AX at 250 V AC
Material	Plate: PC (polycarbonate), white Dolly: PC (polycarbonate), white Base: PA66, black
Embedding depth	12.5 mm
Height	87 mm
Width	87 mm
Depth	29.1 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	SS 227-1 GB 16915.1 BS EN 60669-1 IEC 60669-1 MS IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Packaging

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

EU RoHS Directive

[Compliant By Exemption](#)

Use Again



Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No