

Product datasheet

Specifications



S-Classic - 250V 20AX - 2-pole switch with neon - 1 gang - white

E32D20NA_WE

Main

Range	S-Classic
Product or component type	Switch
Device application	Control
Switch application	Lighting
Quantity per set	Set of 1

Complementary

Control type	Rocker
Actuator	Rocker
Switch function	2-pole
Number of gangs	1 gang
Pilot light	Red neon indicator
Device mounting	Flush Surface
Rated current	20 AX at 250 V AC
Material	Plate: PC (polycarbonate), white Dolly: PC (polycarbonate), white Base: PA66, black
Embedding depth	18.7 mm
Height	87 mm
Width	87 mm
Depth	35.1 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	GB 16915.1 IEC 60669-1 SS 227-1 MS IEC 60669-1 BS EN 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	22 cm
Package 1 Width	32.5 cm
Package 1 Length	49.5 cm
Package 1 Weight	90.5 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	19 cm
Package 2 Length	10 cm
Package 2 Weight	905 g
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	22 cm
Package 3 Width	32.5 cm
Package 3 Length	49.5 cm
Package 3 Weight	9050 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	8 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.7 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	8 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Packaging

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Again



Repack and remanufacture

Recyclability potential, in %	29
End of life manual availability	No need of specific recycling operations
Take-back	No