



10A 250V 1 Gang Switched Universal Socket, White

E8215US_WE

Main

Product or component type	Power socket-outlet
Switch function	Switch
Rated current	10 A at 250 V AC 50 Hz
Number of gangs	1 gang
load type	No inductive load
Cover frame colour tint	White

Complementary

Wiring device mounting	Surface Flush
Outlet poles configuration	2P universal 2P china
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Switch: pillar terminals Socket: clamp terminal
Clamping connection capacity	2 x 2.5 mm² for solid cable(s)
Width	87 mm
Height	87 mm
Depth	8.8 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	GB 2099.1-2008 IEC 60884-2-3 GB 16915.1-2003

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.22 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Weight	102.27 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15.0 cm
Package 2 Length	19.0 cm
Package 2 Weight	818.16 g
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21.0 cm
Package 3 Width	32.5 cm
Package 3 Length	50.0 cm
Package 3 Weight	8181.6 g