

Product datasheet

Specifications



AvatarOn, 2 switches, 16AX, 250V, 1 way, LED, White

E8332DMS_WE

Main

Range	AvatarOn
Product or component type	Switch
Device application	Control
load type	Fluorescent lamp Incandescent lamp Inductive Resistive
Colour tint	White

Complementary

Device presentation	Complete product
Rated current	16 AX at 250 V AC 50/60 Hz
Switch function	1-pole 1-way
Number of gangs	2 gangs
Number of rocker	2
Local signalling	On: LED indicator, LED (amber)
Device mounting	Flush Surface
Connections - terminals	Brass terminal
Clamping connection capacity	3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 4 x 1.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s)
Marking	DO NOT DISTURB Clean up symbol
IP degree of protection	IP20
Width	86 mm
Height	86 mm
Depth	34.2 mm

Environment

Maximum ambient air temperature for operation	45 °C
Operating altitude	2000 m
Relative humidity	0...95 %

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	SS 227-1
	MS IEC 60669-1
	BS EN 60669-1
	IEC 60669-1
Environmental characteristic	UV resistant

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.4 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	113 g
Unit Type of Package 2	BB1
Number of Units in Package 2	60
Package 2 Height	21 cm
Package 2 Width	30 cm
Package 2 Length	39.5 cm
Package 2 Weight	7.58 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant By Exemption](#)

Use Again



Repack and remanufacture

End of life manual availability

No need of specific recycling operations