

S-Classic - 1-way switch - 6 gangs - white - redesign



ET36_1_2AR_WE

Main

Range	S-Classic
Product or component type	Switch
Switch application	Lighting
Quantity per set	Set of 1

Complementary

Control type	Rocker
Actuator	Rocker
Switch function	1-way
Number of gangs	6 gangs
Device mounting	Flush Surface
Rated current	10 AX at 250 V AC
Number of terminals	2
Material	Plate: PC (polycarbonate), white Dolly: PC (polycarbonate), white Base: PA66, black
Embedding depth	12.3 mm
Height	87 mm
Width	147 mm
Depth	28.9 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	MS IEC 60669-1 IEC 60669-1 BS EN 60669-1 SS 227-1 GB 16915.1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.8 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	8.6 cm
Package 1 Length	15 cm
Package 1 Weight	184.5 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	9 cm
Package 2 Width	14.8 cm
Package 2 Length	18 cm
Package 2 Weight	922.5 g
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	20.3 cm
Package 3 Width	30.5 cm
Package 3 Length	47.3 cm
Package 3 Weight	9565 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Total lifecycle Carbon footprint	1 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.3 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Packaging	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Halogen free product

Use Again

Repack and remanufacture	
Recyclability potential, in %	32
End of life manual availability	No need of specific recycling operations
Take-back	No